

1 F O R R E H A B P O W E R



Q6 EDGE® HD
shown in *Midnight Blue*
with *iLevel®* technology

Q6 edge[®] HD

With features like standard 4-pole motors, Mid-Wheel 6[®] Drive Design and ATX Suspension, the Q6 Edge[®] HD is engineered to meet the performance needs of the most active user.

The Q6 Edge HD accepts a complete range of seating and electronics options to deliver exceptional rehab capability at an excellent value, and is available with our *iLevel[®]* technology.

QUANTUM[®]

Specifications

DRIVE WHEELS	Standard: 14" Run flat Optional: 14" Pneumatic 14" Knobby
CASTER WHEELS	Front: 6" Solid Rear: 6" Solid
ANTI-TIP WHEELS	N/A
MAXIMUM SPEED ²	Up to 4.7 mph
GROUND CLEARANCE	3" (frame center)
TURNING RADIUS ³	19.75"
OVERALL LENGTH	35.6" without foot riggings
BASE WIDTH	26.25"
SEATING SIZES ¹⁶	
Synergy®/Static Seat	Width: 20-32" Depth: 20-28"
TRU-Balance® 3 HD Power Tilt	Width: 20-32" Depth: 20-25"
TRU-Balance® 3 HD Lift & Tilt	Width: 20-24" Depth: 20-25"
SEAT-TO-FLOOR HEIGHTS	
Synergy®/Static Seat ⁶	17.5-19.5"
TRU-Balance® 3 HD Power Tilt ⁶	18.5-20.5"
TRU-Balance® 3 HD Lift & Tilt ⁶	17.75-19.75"
MANUAL TILT/RECLINE ⁷	No
BATTERY SIZE ⁴	Group 24
BATTERY WEIGHT ⁹	52 lbs.
AVAILABLE ELECTRONICS ⁸	120A Q-Logic 3 EX 75A Q-Logic NE+ 75A Q-Logic NE
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	4-Pole 4.7 mph ¹
WEIGHT CAPACITY ⁵	450 lbs. ¹⁰
BASE WEIGHT	143.5 lbs.
MEDICARE CODE COVERAGE	Group 3: HD (K0850/K0851), Single Power HD (K0858), Multiple Power HD (K0862)

- 1) Standard
- 2) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
- 3) Without front riggings
- 4) Battery capacity may change when adding power positioning systems.
- 5) Weight capacity is dictated by the selection of seating.
- 6) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
- 7) The Synergy® Manual Tilt weight capacity is 75 lbs. and maximum dimensions are 14" W x 14" D. Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
- 8) All Quantum Rehab® units can be ordered with specialty controls
- 9) Battery weight may vary +/- 3 lbs. based on manufacturer.
- 10) Weight capacity is reduced to 400 lbs. with the iLevel® power adjustable seat height
- 11) A minimum seating size of 20"x20" is required with iLevel®. iLevel® maximum seating size is 24" x 25".

Features

- Mid-Wheel 6® allows six wheels on the ground for maximum stability
- Low impact OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters and semi-independent rear caster beam for enhanced performance over more varied terrain
- iLevel® option enables up to 10" of seat elevation while at walking speed (up to 3.5 mph)^{10,11}

Options

- iLevel® power adjustable seat height^{10,11}
- TRU-Balance® 3 (450 lbs.) HD Tilt, HD Recline, and HD Tilt & Recline
- Q-Logic 2 Drive Control System
- USB mobile device charger
- Swing-away joystick mount
- LED fender lights (standard with iLevel®)

Colors

SEAT BACKS for units without TRU-Balance® 3 are only available in *Back in Black*.

